

Preference[®]



decorum series

NEW Frameless Design with Magnetically-Attached Grille

K-5LCRSd In-Wall 2-way LCRS

Specifications:

- 5-1/4" Rectangular **Frameless**
- Frequency Response: 45Hz - 21kHz \pm 3 dB
- Power Handling: 50 watts nom. 100 max.
- Sensitivity: 90dB 1 watt / 1 meter
- Tweeter: 1" Tetoron[®] soft dome pivoting
- Impedance: 8 ohms nominal

Features:


- Woven Kevlar[®] woofers with butyl rubber surrounds
- Baffle mounted mid & high frequency acoustic compensation / EQ switches
- Industry leading superior clamp-ring mounting system
- High-grade crossovers with polyswitch overdrive protection
- High temperature Polyimide voice coils
- New linear high-excursion design
- Phase plug pole piece extensions
- Sold and shipped individually
- AIB ribbed baffle design
- Vibration-free grille
- IR knockouts



Dimensions:

- Overall Dimensions: 9" x 15-3/4"
- Cut-Out: 7-7/8" x 14-7/16" x 3-1/4" D

Optional Pre-Construction Bracket



Rev. C

Preference[®]
(775) 355-0405 + Fax: (775) 355-0646
www.preference-audio.com + info@preference-audio.com

View the entire
Preference
Product Line:

