

Certain fine loudspeakers in the audio industry become *benchmarks* of sound quality or *reference* standards by which authoritative industry experts judge all others.

Preference® architectural loudspeakers are the new mark of excellence.

You will find no greater value.

The Architectural Loudspeaker:

Preference®

K-6LCRS

6-1/2" 2-way round **15 Degree Angled**
Frequency response: 42 Hz - 21kHz ± 3 dB
Power handling: 50 watts nom. 100 max.
Sensitivity: 90dB 1 watt / 1 meter
8 ohm nominal
Overall dimension: 10-3/4" round
Cut-out: 9-1/4" round x 5" deep
Pre-construction bracket: **RIR-615**

K-8LCRS

8" 2-way round **15 Degree Angled**
Frequency response: 35 Hz - 21kHz ± 3 dB
Power handling: 60 watts nom. 120 max.
Sensitivity: 91dB 1 watt / 1 meter
8 ohm nominal
Overall dimension: 12-7/8" round
Cut-out: 11-1/2" round x 5-3/4" deep
Pre-construction bracket: **RIR-815**

FEATURES

- 15 degree angled baffles significantly enhance cinematic sound staging when room layouts dictate ceiling mounted loudspeakers
- Wide mouth baffle surfaces are covered with Anti-Diffractive foam for very "open" and uninterrupted sound
- Tetoron® soft dome pivoting tweeters
- Kevlar woofers with butyl surrounds
- Mid & high frequency EQ switches
- Polyswitch overdrive protection

ISO 9002 Registered Factory

Lifetime Limited Warranty

OEM SYSTEMS COMPANY, INC.

(775) 355-0405 + Fax: (775) 355-0646

www.preference-audio.com + info@preference-audio.com

Product materials & specifications are subject to change / improvement



K-6LCRS

